

Product Properties

Material	High-Density Polyethylene (HDPE)
Ring Stiffness	$\geq 4\text{kN/m}^2$
Temperature Range	-40°C to 60°C
Standards Compliance	Conforms to IS 16098 Part II


Pipe Sizes: Available in diameters ranging from 100mm to 300mm



100mm




150mm



200mm



250mm



300mm

JK POLYEXTRUSION DWC PIPES

Sy.No.15/c, Chinnapuravolu-Village, Madhiritapally-Mo, Medchal-Malkajgiri-Dist, Telangana-500101
(IS: 16098 PART II) (Certified with ISO 9001:2015)

SIZES AND DIAMETER SPECIFICATIONS

Sl.No	NOMINAL SIZE IN MM	INNER DIAMETER IN MM	CLASS	LENGTH
1	100	100	SN4 / SN8	6 mtrs
2	150	150	SN4 / SN8	6 mtrs
3	200	200	SN4 / SN8	6 mtrs
4	250	250	SN4 / SN8	6 mtrs
5	300	300	SN4 / SN8	6 mtrs

Product Applications



Cable Protection:
Ideal for underground power and telecommunication



Drainage & Sewage Systems:
Widely used for drainage and waste management



Storm Drainage:
Suitable for managing heavy rainwater.



Road & Rail Infrastructure:
Used for under-road drainage solutions.



Get in Touch

We're here to help you with all your plastic extrusion needs. Contact us via phone, email, or visit our facility to discuss your project in detail.

Ready to take the next step? Visit our office, or give us a call to discuss how we can assist with your project.

Marketing & Sales



+91 6303786339 | +91 9618255155
+91 9545152456

For Assistance



+91 9347586993



jkpolyextrusion@gmail.com

Corporate Office & Factory Address



16/c, chinnaparvathapur Village, Muduchintalapally mandal,
Medchal-Malkajgiri-500078

