



GST: 36AATFJ2764K1ZP



Est.2023

JK Polyextrusion

Innovating Excellence in Extrusion Solutions

Certified with ISO 9001:2015

JK Polyextrusion is dedicated to providing industry-leading plastic extrusion solutions. With a focus on precision engineering, our commitment to quality has positioned us as a trusted name across multiple industries.



JK-UPVC

Product Description

Our UPVC Pipes are robust, lightweight, and highly resistant to corrosion and chemical reactions. These pipes are designed for long-term performance and minimal maintenance, making them an ideal choice for water distribution, agriculture, and drainage systems.

Why Choose JK Polyextrusion UPVC Pipes?


At JK Polyextrusion, our UPVC pipes stand out due to their superior quality, durability, and cost-effectiveness.

We ensure:

- **Corrosion Resistance:** Our pipes are resistant to rust, chemicals, and weather, making them ideal for water supply and plumbing.
- **Leak-Proof Joints:** Using advanced solvent cement or push-fit joints, our UPVC pipes guarantee a secure, leak-proof system.
- **Eco-Friendly:** Non-toxic and lead-free, safe for potable water and environmentally friendly.
- **Low Maintenance:** With a smooth internal surface and high impact strength, our UPVC pipes require minimal maintenance, saving you time and money.



Certified with ISO 9001:2015



CM/L-6300114286



Product Properties

| | |
|----------------------|---|
| Material | Unplasticized Polyvinyl Chloride (UPVC) |
| Pressure Ratings | Up to 16 bar |
| Temperature Range | -5°C to 60°C |
| Density | 1.40 g/cm ³ |
| Tensile Strength | ≥ 45 MPa |
| Elongation at Break | ≥ 50% |
| Standards Compliance | Conforms to IS 15328:2003 |

Pipe Sizes: Available in diameters ranging from 63mm to 200mm



63mm



75mm



90mm



110mm



125mm



160mm



200mm

| JK POLYEXTRUSION UPVC PIPES | | | | | | | | | | | |
|--|-----------------------|----------------------------|--------|--------|------|---------------------------------|------|----------------------------------|------|----------------------------------|------|
| S/N: No.16/C, Chinnaganavapur-Village, Mudchintalapally-Mid, Medchal-Malkajgiri-Dist, Telangana-500101 | | | | | | | | | | | |
| (Confirms IS 15328:2003) (Certified with ISO 9001:2015) | | | | | | | | | | | |
| Sr. No. | Nominal Diameter (MM) | Mean Outside Diameter (MM) | | | | Nominal Ring Stiffness | | | | | |
| | | | | | | SN2 (SDRS1) Wall Thickness (MM) | | SN4 (SDR 41) Wall Thickness (MM) | | SN8 (SDR 34) Wall Thickness (MM) | |
| | | MM | Min. | Max. | Avg. | Min. | Max. | | | | |
| 1 | 63 | 63.00 | 63.30 | 63.15 | | | | | | 2.70 | 3.30 |
| 2 | 75 | 75.00 | 75.30 | 75.15 | | | | | | 2.80 | 3.30 |
| 3 | 90 | 90.00 | 90.30 | 90.15 | | | | | | 2.90 | 3.40 |
| 4 | 110 | 110.00 | 110.40 | 110.20 | | | | | | 3.20 | 3.70 |
| 5 | 125 | 125.00 | 125.40 | 125.20 | | | 3.20 | 3.70 | 3.70 | 3.70 | 4.40 |
| 6 | 160 | 160.00 | 160.50 | 160.25 | 3.20 | 3.70 | 4.00 | 4.60 | 4.70 | 5.40 | 5.40 |
| 7 | 200 | 200.00 | 200.60 | 200.30 | 3.90 | 4.50 | 4.80 | 5.60 | 5.90 | 6.70 | 6.70 |

Product Applications



Industrial Fluid Transportation:
Suitable for carrying chemicals and industrial



Drainage & Sewage Systems:
Durable for waste management and



Water Supply Systems:
Ideal for residential commercial



Agricultural Irrigation:
Efficient for drip and sprinkler irrigation



Get in Touch

We're here to help you with all your plastic extrusion needs. Contact us via phone, email, or visit our facility to discuss your project in detail.

Ready to take the next step? Visit our office, or give us a call to discuss how we can assist with your project.

Marketing & Sales

+91 6303786339 | +91 9618255155
+91 9545152456

For Assistance

+91 9347586993

 jkpolyextrusion@gmail.com

Corporate Office & Factory Address

 16/c, chinnaparvathapur Village, Muduchintalapally mandal,
Medchal-Malkajgiri-500078

